

FR4 standard

		0,2mm	0,4mm	0,5mm	0,6mm	0,8mm	1,0mm	1,2mm	1,6mm	2,0mm	2,4mm	3,2mm	Remarques
FR4 TG 130°	2*18μ				X	X	X	X	X	X	X	X	Referenz : DURAVÉR 104.
	2*35μ	X	X	X	X	X	X	X	X	X	X	X	
	2*70μ					X	X		X		X		
	2*105μ						X		X	X			
	1*35μ					X			X		X		
	1*70μ								X				
	1*105μ								X				

FR4 Hohe Temperatur

		0,2mm	0,4mm	0,5mm	0,6mm	0,8mm	1,0mm	1,2mm	1,6mm	2,0mm	2,4mm	3,2mm	Bemerkungen
DURAVÉR 117 HTG 170°	2*17μ				X								
	2*35μ								X				
FR4 IS 410 HTG 180°	2*18μ					X	X		X				
	2*35μ					X			X				

Hohe Frequenz

		0,2mm	0,4mm	0,5mm	0,6mm	0,8mm	1,0mm	1,2mm	1,6mm	2,0mm	2,4mm	3,2mm	Bemerkungen
25N Hte Fréquence	2*18μ			X		X			X				für RF Anwendungen

Andere Material

		0,2mm	0,4mm	0,5mm	0,6mm	0,8mm	1,0mm	1,2mm	1,6mm	2,0mm	2,4mm	3,2mm	Bemerkungen
CEM1	2*35μ						X		X				
	1*35μ					X			X				
CEM3	2*18μ								X				
FR4 104KF	2*35μ								X				tracking index 400. PCB im ätzenden Umwelt
FR2 KC250	1*35μ								X				